
RANDOM ASHLAR

WALLING

ECO OUTDOOR®

FLOORING • WALLING • FURNITURE

MELBOURNE SYDNEY BRISBANE ADELAIDE PERTH
T. 1300 13 14 13 ECOOUTDOOR.COM.AU



WORKING WITH VERTICAL AND HORIZONTAL LINES

From small rural villages in Spain and provincial France through to modern Australian architecture and landscape design, Ashlar stone walling is celebrated for its raw structured form. From internal fireplaces to sweeping retaining walls, our Random Ashlar stone cladding range is a classic, timeless stone building material.

The earthy organic texture of Random Ashlar brings warmth and textural relief to modern architecture while capping and corner finishing details are the key to ensuring an authentic result.

Hard and durable for internal and external applications, by adjusting the grout joint colour and spacing size, you can dramatically alter the design impact. Consider recessing the grout for a bolder design statement emphasising the structure and form of the stone.





Apollo



Clancy




Coolum



Newport

—
A selection of high resolution 3D textures is available at www.ecooutdoor.com.au



-
- 1. Apollo
 - 2. Clancy
 - 3. Coolum
 - 4. Coolum
-

SIZES

Apollo



Clancy



Coolum



Newport



Corners



Capping



—
For more downloadable imagery visit www.ecooutdoor.com.au

Apollo, Coolum	<i>Weight (kg/m²)</i>	<i>Packing Details (m²/crate)</i>	Newport	<i>Weight (kg/m²)</i>	<i>Packing Details (m²/crate)</i>
Walling Split face veneer split on 5 sides and sawn on the back Random square and parallelogram shaped stone Lengths up to 400mm Heights up to 250mm Thickness 15-35mm	70	5	Walling Split face veneer split on 5 sides and sawn on the back Random square and rectangle shaped stone pieces up to 300x300mm Thickness 30-50mm	85	10
Corners L shaped corner pieces Random lengths up to 300mm Random heights up to 240mm Thickness 15-35mm	25	12 (4x3LM)	Corners L shaped corner pieces Random lengths up to 300mm Random heights up to 240mm Thickness 30-50mm	35	16 (4x4LM)
Clancy			Capping Textured finish to top surface, split on the sides and sawn on the bottom surface Length 400mm Width 290mm Thickness 30-50mm	120	60 units
Walling Split face veneer split on 5 sides and sawn on the back Random square and rectangle shaped stone pieces up to 300x300mm Thickness 20-40mm	90	5			
Corners L shaped corner pieces Random lengths up to 250mm Random heights up to 240mm Thickness 20-40mm	35	12 (4x3LM)			
Capping Textured finish to top surface, split on the sides and sawn on the bottom surface Length 400mm Width 290mm Thickness 30-50mm	130	50 units			

Typically these products are adhered to a concrete or block wall with a suitable tile adhesive. Use of mechanical fixings may also be required. Corner details are slightly different for each stone type. When working out quantities required for a wall, you need to know the face in m² to be covered and the number of lineal metres of corners required. For further information, installation tips and pricing please call a showroom on 1300 13 14 13.