
PORPHYRY

FLOORING

ECO OUTDOOR®

FLOORING • WALLING • FURNITURE

MELBOURNE SYDNEY BRISBANE ADELAIDE PERTH
T. 1300 13 14 13 ECOOUTDOOR.COM.AU

UNRIVALLED DURABILITY

A stone hailed since ancient times for its durability and aesthetic appeal, iconic architects such as Harry Seidler and Renzo Piano continue to utilise porphyry as one of their favourite materials.


Porphyry has a superior structural matrix for exceptional strength. This, coupled with the irregular-shaped pieces we offer, make Porphyry ideal for Cobblestones, Filetti and Crazy Paving flooring options. Typically, porphyry is not quarried in large blocks like granite but instead sheers off and has a natural split finish which is inherently non-slip, making it an ideal product for commercial applications.

Eco Outdoor's Porphyry range features varying colours resulting in beautiful tones of red, grey and gold that differ from piece to piece and therefore are extremely forgiving, requiring minimal maintenance.





Baguette



Cobblestones



Crazy Paving



Filetti



Random Lengths



Split Pebbles


—
A selection of high resolution 3D textures is available at www.ecooutdoor.com.au




-
- 1. Split Pebbles
 - 2. Random Length + Cobbles
 - 3. Porphyry Filetti
 - 4. Baguette
-

SIZES


Cobblestones




Random Lengths




Crazy Paving




Split Pebbles



Filetti



Baguette



—
For more downloadable imagery visit www.ecooutdoor.com.au

Porphyry	<i>Weight (kg/m²)</i>	<i>Packing Details (m²/crate)</i>
Cobbles		
40-60x40-60mm, 40-60mm	100	12
100x100mm, 20-40mm	80	16.5
Random Lengths		
150-300x150mm, 20-30mm	70	20
Crazy Paving		
Various sizes, 20-40mm	70	16
Split Pebbles		
Various sizes, 60-80mm		
Filetti		
Various sizes, width 30-80mm, thickness 30-50mm	110	11
Baguette		
Various sizes, length 150-400mm, width 100-120, thickness 50-80mm	130	10
Step Tread		
600x350mm, 30-40mm	100	67 units

Weight for 20-40mm cobbles and crazy paving is approximately 75kg/m².

Given porphyry has variation in thickness this product should ideally be laid on a 25mm wet mortar bed over a concrete slab.

Given Filetti stones have variations in thickness, these products should ideally be laid on a 30mm wet mortar bed over a concrete slab.

Refer to installation tips for further information.

Other random length tiles sizes can be produced on request.

For further information, installation tips and pricing please call a showroom on 1300 13 14 13.